



## Gemini Series Large Format Displays



### Space and Productivity Multiplied

Our Gemini Series color LED backlit display systems double the resolution and eliminate the gap between screens in multi-head display configurations. Allowing the eye to seamlessly glide between images uninterrupted increases productivity and user efficiency. Complete with advanced auto-calibration technology, these wide-screen models enable multi-modality imaging from a single display.

The large, wide-screen displays are equipped with built in front sensors for hands-free automatic precise grayscale calibration, backlight sensors to maintain stability over time, ambient light sensors, auto-report generation and non-conformance alerts via the web.

Additional user friendly features include auto-dimming capability, image pinpointing, cursor wrap, and cursor genie functions – improving workflow and enhancing the user experience.

### About Double Black Imaging and our Image Systems Display Division

We are proud to be the largest display supplier and calibration software developer, creating 100% of our software and performing 100% display system integration in the USA.

Our team has a renowned history of providing the industry's finest customer service, continually acknowledged by thousands of users and IT Professionals who put their trust in us every day.

We are dedicated to developing innovative imaging solutions that greatly improve image quality and stability. Making imaging more efficient and reducing costs are the cornerstones of what DBI stands for.



A division of Double Black Imaging

# G-Series - Technical Specifications



4G



6G

G Series Color	4G	6G
Size	30"	30.4"
Active Display Area H x V	641.28 x 400.8mm / 5.25 x 15.78"	654.360 x 408.576mm / 25.76 x 16.09"
Resolution	2560 x 1600 (4MP)	3280 x 2048 (6MP)
Brightness	700 cd/m <sup>2</sup> Typ.; 350-400 cd/m <sup>2</sup> Recommended Calibrated	720 cd/m <sup>2</sup> Typ.; 350-400 cd/m <sup>2</sup> Recommended Calibrated.
Contrast Ratio	1000:1 Typ.	1000:1 Typ.
Look Up Table	14-bit LUT	
Response Time	6ms Typ.	18ms Typ.
Pixel Pitch	0.2505 x 0.2505 mm	0.1995 x 0.1995 mm
Built In Sensors	Front Sensor, Backlight Sensor, Ambient Light Sensor, Temperature Sensor	
Tilt/Swivel/Height Adjustment	- 5 to +15° tilt   +/- 45° swivel   80mm height adj	
Panel Technology	TFT AMLCD IPS Color, LED Backlit	
Viewing Angle	178° Typ.	
Video Input / USB (1up 1down)	DisplayPort (1), DVI-D (2), USB	DisplayPort (2), DVI-D (2), USB
Power Supply	External for Added Reliability. AC Input to power brick: 100-240V, DC Input to display: 24V	
Power Consumption	160w max./Power save mode < 5w	
Operating Temperature Range	5° to 35°C (41° to 95°F)	
Operational Humidity	15% - 85%	
Storage Temperature	-20° to +60°C (-4° to + 140°F)	
Weight w/ stand (approx)	32 lbs	38 lbs
Dimensions ( W x H x D ) w/stand full height	27.5" x 25.6" x 9.8"	28.3" x 24.7" x 9.8"
Mounting Options	100 x 100 mm VESA	
Safety & Emissions	EN60601-1, IEC60601-1, UL 60601-1:2003 R6.03 / CAN/CSA-C22.2 No.601.1-M90service: cTUVus certificate CCC, CB (NCB Lab.), FCC, IP20, CE	EN60601-1, IEC60601-1, GB4943.1, ANSI/AAMI ES60601-1:2005 + A2(R2012) + A1, CAN/CSA-C22.2 No. 60601-1:14, CE acc to MDD 93/42/EEC (Class I), IP20
Warranty	5-Year standard warranty with Hot Swap	

## Calibration Feedback System – CFS™

- Our industry leading CFS software - Client and Web Manger
- Ensures precise grayscale calibration and confidence
- Provides tools to enhance visibility, efficiency, workflow
- Enables performance monitoring and asset management
- Accurate calibration of both color and gray shades

CFS Software comes standard with every G-Series display.

CURSOR GENIE	CURSOR WRAP	DICOM 3.14	TG-18 VISUAL ACCEPTANCE	CONFORMANCE CHECK	X → ✓
COLOR POINT CALIBRATION	PINPOINT	LUMINANCE CALIBRATE	AMBIENT WARNING	EVENT LOG	REPORT GENERATOR
XX,XXX Hrs	TEMPERATURE	GRAPH GENERATOR	WEB MANAGER	ASSET MANAGER	100% USA BASED SERVICE

## Hassle-Free Services & Support

Overcome technical challenges with our team of experienced engineers and technicians. Whether it's a simple answer or on-site troubleshooting, we can help any time, every time. Accurate and consistent presentation of images is a critical requirement for displays.



**DBI Service Desk**  
Comprehensive  
Technical Support

**Hot Swap**  
Extended Warranty &  
Advanced Replacement Program



[www.doubleblackimaging.com/servicesdesk](http://www.doubleblackimaging.com/servicesdesk)



[www.doubleblackimaging.com](http://www.doubleblackimaging.com) | 303-404-2222

2018 Double Black Imaging | All brands and trademarks are the property of their respective owners.

Specifications are subject to change without notice.