



## Clinical Review 2MP Color Display

### Applications Include:

- CR/DR • CT • MRI • DSA • PET/CT • DSI
- 3D Medical Imaging • Image Fusion
- Nuclear Medicine • CAD • X-Ray



- Built-in Backlight Stabilization System Including LED Backlight
- Embedded front Sensor for Automatic DICOM 3.14 Calibration
- Ultra-Thin True Flat Design
- Includes 3 Year Warranty with Hot Swap

Specifications	CL2MPS+
Display Size	21.3"
Active Display Area	324 x 432mm / 12.75 x 17.0"
Support Color	1.07 Billion
Resolution	1600 x 1200
Pixel Pitch	0.270 x 0.270mm
Brightness	500 cd/m <sup>2</sup>
Contrast Ratio	1800:1 Typical
Viewing Angle	178° Typical
Response Time	16ms Typical
Input Signal Interface	DVI-D 24 pin, DisplayPort 20 pin, VGA D-Sub 15 pin
Size with Stand W x H x D	369 x 507-627 x 235mm / 14.53 x 19.96-24.69 x 9.25"
Weight with Stand	9.2 kg / 20.28 lbs.
Mounting Standard	VESA 100 x 100mm
Power Supply	DC 12V
Power Consumption	50W Maximum
Power Saving	EPA, VESA
MTBF	>50,000 Hours
Warranty	3 Year Warranty

### Hassle-Free Services & Support

Overcome technical challenges with our team of experienced engineers and technicians. Whether it's a simple answer or on-site troubleshooting, we can help any time, every time. Accurate and consistent presentation of images is a critical requirement for radiology displays.



**DBI Service Desk**  
Comprehensive  
Technical Support

**Hot Swap**  
Extended Warranty &  
Advanced Replacement Program



[www.doubleblackimaging.com/servicedesk](http://www.doubleblackimaging.com/servicedesk)